

TECHNICAL DATA



MODEL	FX JET
MAX. TEMP. FORWARD	60°C
HEAT-TRANSFER MEDIUM	Water
MAIN CIRCUITS	4 (Optional 8)
PINS	32 (Optional 64)
TEMPERATURE CONTROL	Monitored
DEIONISER	Integrated and automatically controlled
FLOW MEASUREMENT	Integrated
AIR PRESSURE	Integrated
MANUAL RINSING FUNCTION	Integrated
WATER-PRESSURE MEASUREMENT	Integrated
PIN-BREAK MONITORING	Integrated
CURVE / PIN	Integrated
FAULT DIAGNOSIS	Integrated
FAULT RECORDING	Integrated
PULSE OPERATION MODE	Integrated
TANK CAPACITY [l]	250
DATA MEMORY & TRANSFER	Integrated
TOUCHSCREEN	Removable HMI
COOLER	Inox heat exchanger
PUMP TYPE	Centrifugal pump
MAX. FLOW RATE	100 l/min
POWER CONSUMPTION	5,5 kw
MAX. PRESSURE	24 bar
CONTROL SYSTEM	Siemens SPS
CONNECTION VOLTAGE	400 V / 50 Hz / 32 A
EXT. CONTROL VOLTAGE	Internally generated control voltage DC24V
COMPRESSED AIR CONNECTION	3/8 "
COOLING WATER FITTING	3/8 "
DISTRIBUTOR FITTING	3/8 "
PROTECTION CLASS	IP54
DIMENSIONS W X H X D [mm]	800 x 1700 x 1200
WEIGHT [kg]	500 / 600