

OUR LATEST DEVELOPMENT

As a response to the market demand, Fondarex created a new family of mechanical valves, which presents high evacuation capacities, high reliability, compact sizes and finally a competitive price. Those characteristics have been achieved with the development of the brand new KINETIC Valves.

A MODULAR CONCEPT

7 different evacuation capacities 12mm², 25mm², $40mm^2$, $75mm^2$, $100mm^2$, $200mm^2$ and $300mm^2$ for 4 different valve sizes.

This gives the possibility to start a project for example with a 200mm² profile block and upgrade it with a 300m² profile block if more evacuation capacity is needed, without fully changing the mechanical valve. This is an important financial economy and provides in the same time more flexibility.



KINETIC 12

- Specially designed for Zamac applications
- in the market Up to 200t DCM



KINETIC 40 / 25

- Ultra compact
- design Up to 800t DCM



- castings Structural parts
- Up to 9000t DCM



LOW AND EASY **MAINTENANCE**

We simplified the mechanism and therefore reduced the number of spare parts. Achieving a higher reliability and a lower maintenance costs



INTEGRATED COOLING CIRCUIT

of the valve.

The valves KINETIC 75 / 100 and KINETIC 200 / 300 have an integrated cooling circuit.



REDESIGNED FILTER

A new robust filter for easy and quick maintenance.

>



KINETIC 100 / 75

- High efficiency Up to 2000t DCM



SCOOP OF INVESTEMENT

Fondarex created the KINETIC valve in order to improve the efficiency, the reliability but also in order to propose a new affordable mechanical valve. The investment today in a KINETIC valve is 50% less than a traditional valve, which make it a serious option towards Chill-Blocks.

With the new KINETIC valve, you will get the double evacuation capacity for an unbeatable price.

TECHN	NICAL
DATA	

TECHNICAL DATA	KINETI	DAREX C VALVE	FONE KINETIC	園 DAREX C VALVE /25	KINETIC	DAREX C VALVE	KINETIC	DAREX C VALVE
DCM TONNAGE [t]	20 – 200		80 – 800		200 – 2000		1200 – 6000	
SHOT WEIGHT [kg]	ZN 0,1 – 2		ZN 0,2 – 8 AL 0,2 – 5		ZN 0,8 – 14 AL 0,6 – 15		AL 7 – 50	
DIMENSIONS	Valve block	Profile block	Valve block	Profile block	Valve block	Profile block	Valve block	Profile block
WIDTH [mm]	40	40	55	55	100	100	125	125
DEPTH [mm]	44	20	50	25	75	50	95,5	57,5
HEIGHT [mm]	50	50	65	65	125	125	175	175
WEIGHT [kg]	0,6	0,3	1,3	0,6	6,9	4,3	14,4	8,5

FOR FURTHER INFORMATION

Contact our team members at sales@fondarex.com or your local Fondarex representative.